



RESIDENTIAL ELECTRIC WATER HEATERS

- Foam insulation is CFC-free and has no added colourants
- ¾" NPT water connections with plastic-lined nipples
- Factory-installed T&P valve
- Tamper-resistant drain valve
- Removable anodes
- Insulated base for better energy efficiency
- Thermostatically controlled long life elements

9 year tank models feature:

- Brass drain valve
- Drip tube

BMR ID	Model	Tank Warranty*	Series	SAP SKU	Capacity			Input		Standby Loss	Height	Diameter	Shipping Weight	UPC	Compliant For All Provinces
		Years			IG	USG	L	WATTS	VOLTS	WATTS	IN (CM)	IN (CM)	LB (KG)		
TOP ENTRY															
002-7442	G650SDEQC-30	6	250	100391597	40	50	182	3,000	240	53	49 ¼ (124)	22 (56)	140 (64)	772914625531	√
002-7444	G680TDEQC-45	6	250	100391599	60	80	287	4,500	240	78	59 ¼ (154)	24 (61)	185 (84)	772914673532	√
002-7446	G950SDEQC-30	9	250	100391601	40	50	182	3,000	240	53	49 ¼ (124)	22 (56)	140 (64)	772914625630	√
002-7445	G980TDEQC-45	9	250	100391600	60	80	287	4,500	240	78	59 ¼ (154)	24 (61)	185 (84)	772914673631	√
BOTTOM ENTRY															
002-7447	G650SDEBQC-30	6	250	100391602	40	50	182	3,000	240	65	49 ¼ (124)	22 (56)	140 (64)	772914625739	√
002-7448	G680TDEBQC-45	6	250	100391603	60	80	287	4,500	240	80	59 ¼ (154)	24 (61)	185 (84)	772914673730	√

*In residential applications. Reduced warranty in commercial applications.

Critical parts (i.e. elements and thermostat) warranted for 6 years; all other parts warranted for 1 year



SPACESAVER® ELECTRIC WATER HEATERS

- Foam insulation is CFC free and has no added colourants
- All models are CSA and/or UL approved
- Factory-installed T&P valve
- Personnel protector on all models cover elements and controls
- Meets latest energy efficiency standards
- Removable anodes
- Insulated base for better efficiency
- Thermostatically controlled long life elements

BMR ID	Model	Tank Warranty*	Series	SAP SKU	Capacity		Input		Standby Loss	Height	Diameter	Shipping Weight	UPC	Compliant For All Provinces
		Years			IG	USG	WATTS	VOLTS	WATTS	IN (CM)	IN (CM)	LB (KG)		
TOP ENTRY SINGLE ELEMENT MODELS														
062-3254	SS025SE-15	6	100	100290016	2	2.5	1,440	120*	N/A	14 ½ (37)	10 ¾ (26)**	17 (8)	770110060323	✓
080-1311	SS04SE15	6	100	100290017	3	4	1,440	120*	N/A	19 ¼ (49)	10 ¾ (26)**	20 (9)	770110060347	✓
BOTTOM ENTRY SINGLE ELEMENT MODELS														
062-3236	SS06SEB15	6	100	100118722	5	6	1,500	120	N/A	15 ¼ (39)	14 ¼ (36)	35 (16)	770110034027	✓
062-3184	SS06SEB30	6	s.o.	100118723	5	6	1,500	240**	N/A	15 ¼ (39)	14 ¼ (36)	35 (16)	770110034034	✓
062-3102	SS12SEB-15	6	s.o.	100118458	9	12	1,500	120	N/A	22 ¼ (58)	16 (41)	55 (25)	770110034041	✓
062-3218	SS12SEB-30	6	100	100118461	9	12	3,000	240**	N/A	22 ¼ (58)	16 (41)	55 (25)	770110034058	✓
062-3227	SS620SSEB-30	6	100	100118753	14	19	3,000	240**	51	25 ½ (65)	20 (51)	65 (30)	671657165796	✓
062-3175	SS630SSEBN-30	6	100	100211179	22	30	3,000	240**	48	30 (76)	22 (56)	101 (46)	671657200749	✓
TOP ENTRY DOUBLE ELEMENT MODELS														
062-3148	SS640SDE3-30	6	100	100210892	30	40	3,000	240**	54	50 (127)	20 (51)	103 (47)	671657199838	✓
062-3245	SS650SDE-30	6	250	100210795	40	50	3,000	240**	53	48 ¼ (125)	22 (56)	125 (57)	671657216603	✓
062-3111	SS680TDE-45	6	250	100210862	60	80	4,500	240***	78	60 ½ (152)	24 (61)	170 (77)	671657216610	✓

*In residential applications. Reduced warranty in commercial applications. Parts warranted for 1 year.

**Depth. Width is 11 ¾ (30)

***Depth. Width is 15 ¾ (40)

+Plug-in model

++Model is dual-rated. At 208V wattage is 2253.

+++Model is dual-rated. At 208V wattage is 3380.

SPECIAL ORDER**RESIDENTIAL CONNECTED ELECTRIC WATER HEATERS**

- Exclusive TankSaver® design for extended inner tank life
- Available in 50 and 80 USG capacities
- Meets the NRCAN standby loss requirements
- Element "Dry-Fire" protection
- Leak detection sensor sounds alarm when water is detected
- Replaceable anode rods have a stainless steel core that provides superior tank protection far longer than standard anode rods
- Electronic control display with diagnostic feedback and two operating modes

BMR ID	Model	Tank Warranty*	SAP SKU	Capacity			Input		Height	Diameter	Shipping Weight	UPC	Compliant For All Provinces
		Years		IG	USG	L	WATTS	VOLTS	IN (CM)	IN (CM)	LB (KG)		
TOP ENTRY													
002-9695	G950SDEE-30	9	100375486	40	50	189	3000*	240	49 ¼ (125)	23 (59)	117 (53)	770110070667	✓
002-9696	G980TDEE-45	9	100375613	60	80	287	4500**	240	60 ½ (154)	24 (61)	174 (79)	770110070711	✓

*In residential applications. Reduced warranty in commercial applications.

+Model is dual-rated. At 208V wattage is 2253.

++Model is dual-rated. At 208V wattage is 3500.

SPECIAL ORDER**VOLTEX® HYBRID CONNECTED ELECTRIC HEAT PUMP**

- Available in 50 and 80 USG capacities
- Up to a 3.88 Uniform Energy Factor (UEF) conserves energy and exceeds ENERGY STAR® qualifications
- Smart sensor alerts user in the event a leak does occur for added peace of mind
- Select from multiple operating modes: Hybrid, Heat Pump, Electric or Vacation
- Vacation mode reduces operating costs and provides freeze protection during extended absence
- Our anode rods have a stainless steel core that extends the life of the anode rod allowing superior tank protection far longer than standard anode rods.
- User-friendly electronic interface allows easy control of temperature, operating mode and diagnostics
- Optional air duct adapter kit permits installation in confined spaces
- Backup electric elements can supplement the heat pump depending on operating mode, environmental conditions and hot water demand

BMR ID	Model	Tank Warranty*	SAP SKU	Capacity			Input		UEF	Height	Diameter	Shipping Weight	UPC	Compliant For All Provinces
		Years		IG	USG	L	WATTS UPPER/LOWER	VOLTS		IN (CM)	IN (CM)	LB (KG)		
HYBRID ELECTRIC														
002-9697	HPTS-50	10	100350427	40	50	189	4500/4500	208/240	3.80	63 (160)	22 (56)	196 (89)	671657272500	√
002-9699	HPTS-80	10	100350429	60	80	303	4500/4500	208/240	3.88	69 (175)	26 ½ (67)	302 (137)	671657272524	√

*In residential applications. Reduced warranty in commercial applications. Parts warrantied for 10 years.